

Liberty Suppressors

www.libertycans.net

Specification Sheet for 9mm Pistol Suppressor

Model name: Centurion

Caliber: 9mm, 300 BLK

Weight: 7.9oz. Suppressor Only / 12.5 oz. with booster installed.

Length / Diameter: 5.3" Silencer Only / 6.5" with Booster

Materials: Stainless Steel / Titanium

Attachment: Modular mounting system.

Average DB reduction: 24dB dry – 32dB wet

Description: This suppressor is specifically engineered for the 9mm pistol platform. We designed this silencer specifically for pistol use, we also wanted it to be versatile so we designed it to be compatible with the Mystic family of mounting solutions, this gives it the full array of mounts that are available for the Mystic X and shortens the overall length of the system 3 inches. Combining small footprint, lightweight, and excellent suppression, we feel that the Centurion will be right at home on the nightstand as well as the range.

LIBERTY SUPPRESSORS

113 GUNSMOKE TRAIL

TRENTON GA 30752

(706) 661-6911

WWW.LIBERTYCANS.NET

info@libertycans.net

Mystic X family disassembly / cleaning instructions

First, remove the suppressor from the weapon.

Remove any attachments from the rear of the suppressor module. Second, remove the tube retaining ring from the rear of the suppressor module. The Ring Wrench can help with this if it's too carbon locked or was installed too tightly.

At this point, it helps to wet the inside of the core with some penetrating oil such as Kroil Oil. This will drastically help in removal of components.

Push the core assembly out of the tube by using the disassembly tool (sold separately) or a wooden dowel.

Clean the core with normal solvents, ultrasonic cleaners, or sand blast the core. If you do sand blast the core, be sure to protect the end and the front of the core using electrical tape or something similar.

Reassemble in reverse order, be sure to align the wavelok with the feature on the tube during reassembly. The user may also apply some anti-sieze or other lubricant to the parts to prevent galling of the threaded surfaces. Do not over torque the lock ring, as its only function is to retain the tube and it therefore doesn't need very much force.

Thank you for your choosing Liberty Suppressors!

- **The Liberty Team**