

LIBERTY SUPPRESSORS

113 GUNSMOKE TRAIL
TRENTON, GA 30752-5156

Phone: 706-661-6911 FAX: 706-229-6400

www.libertycans.net

info@libertycans.net

Multi-Purpose Suppressor

Model: Cosmic

Caliber: Over 60 Calibers: See website for a complete listing

Weight: Approximately 9.5 ounces

Length / Diameter: 8" x 1.375"

Material: Stainless Steel / Titanium

Attachment: Multiple Styles

Approx. DB Reduction: 24db

MSRP: \$799

Over 60 Caliber Ratings including 10mm AUTO!
(Lots of T/C Calibers now to pick from)

- 9.5 Ounces (which is almost the weight of our previous aluminum design)
- New ock ring can be easily removed
- New front profile redirects gas as well as reducing sound signature.
- New baffle design improves performance while reducing weight

This is the most versatile silencer ever constructed for the 45ACP cartridge. It has applications for the recreational shooter, competition shooter, as well as the hunter and even law enforcement circles.

With so many calibers and so many mounting solutions, why wouldn't you choose a Cosmic as your first 45 suppressor?

LIBERTY SUPPRESSORS

113 GUNSMOKE TRAIL

TRENTON GA 30752

(706) 661-6911

WWW.LIBERTYCANS.NET

info@libertycans.net

Mystic X family disassembly / cleaning instructions

First, remove the suppressor from the weapon.

Remove any attachments from the rear of the suppressor module. Second, remove the tube retaining ring from the rear of the suppressor module. The Ring Wrench can help with this if it's too carbon locked or was installed too tightly.

At this point, it helps to wet the inside of the core with some penetrating oil such as Kroil Oil. This will drastically help in removal of components.

Push the core assembly out of the tube by using the disassembly tool (sold separately) or a wooden dowel.

Clean the core with normal solvents, ultrasonic cleaners, or sand blast the core. If you do sand blast the core, be sure to protect the end and the front of the core using electrical tape or something similar.

Reassemble in reverse order, be sure to align the wavelok with the feature on the tube during reassembly. The user may also apply some anti-sieze or other lubricant to the parts to prevent galling of the threaded surfaces. Do not over torque the lock ring, as its only function is to retain the tube and it therefore doesn't need very much force.

Thank you for your choosing Liberty Suppressors!

- **The Liberty Team**