

Liberty Suppressors

www.libertycans.net

Specification Sheet for Infiniti X Suppressor

Model name: Infiniti X

Caliber: Caliber list is as follows:

All rimfire

All pistol calibers up to 9mm bore.

All rifle calibers up to 300 WIN MAG with the following restrictions :

- 223/7.62x39/6.8SPC etc. - 11" or longer semi auto only,
- 308/30-06 family etc. - 18" or longer semi auto only,
- 300WIN MAG and equivalent energy - 22" barrels and longer semi auto only.

All rifle calibers can be used with the LoPro FBA except the WIN MAG family which requires the full size FBA.

Weight: 7.7 ounces!

Length / Diameter: 8.3" x 1.375" Diameter

Materials: ALL Titanium with alloy retaining ring

Attachment: Modular

Average DB: 30 – 35dB depending on conditions

Description: This suppressor is specifically engineered for a smooth user experience. We wanted a can that solved the problem of modular and be lightweight at the same time. This suppressor is for the general enthusiast that wants a highly adaptable suppressor that is light weight and provides exceptional suppression. Working equally as well on rimfire and pistol calibers, it is still at home on your favorite hunting rifle and AR15. Take on those pesky deer in your garden or the steel plates at the local rifle club. To get yours, call us at 706-661-6911 or find us on the web at the address above!

LIBERTY SUPPRESSORS

113 GUNSMOKE TRAIL

TRENTON GA 30752

(706) 661-6911

WWW.LIBERTYCANS.NET

info@libertycans.net

Mystic X family disassembly / cleaning instructions

First, remove the suppressor from the weapon.

Remove any attachments from the rear of the suppressor module. Second, remove the tube retaining ring from the rear of the suppressor module. The Ring Wrench can help with this if it's too carbon locked or was installed too tightly.

At this point, it helps to wet the inside of the core with some penetrating oil such as Kroil Oil. This will drastically help in removal of components.

Push the core assembly out of the tube by using the disassembly tool (sold separately) or a wooden dowel.

Clean the core with normal solvents, ultrasonic cleaners, or sand blast the core. If you do sand blast the core, be sure to protect the end and the front of the core using electrical tape or something similar.

Reassemble in reverse order, be sure to align the wavelok with the feature on the tube during reassembly. The user may also apply some anti-sieze or other lubricant to the parts to prevent galling of the threaded surfaces. Do not over torque the lock ring, as its only function is to retain the tube and it therefore doesn't need very much force.

Thank you for your choosing Liberty Suppressors!

- **The Liberty Team**